



ORIENTATION AS PER P&ID DIAGRAM FOR OPTIMUM DRAINABILITY.

MAINLINE SIZE	A	B	C	D	øE	øF	BODY WEIGHT
mm	mm	mm	mm	mm	mm	mm	Kgs
DN80	50.8	50.0	46.5	64.0	76.1	72.9	21.0
DN100	101.6	50.0	58.8	76.0	101.6	97.6	28.7

The information on this sheet is Private and Confidential and is the property of Crane Process Flow Technologies Limited and must not be published directly or indirectly in any manner whatsoever without the written permission of the Company and must not be used in any way detrimental to their interests.
© Crane Process Flow Technologies

CRANE Process Flow Technologies
A Crane Co. Company

Saunders
The Science Inside

Title
SCHEDULE OF LEADING DIMENSIONS FOR DN80
WEIR 'T' BODY COMPLETE WITH :
MAINLINE : BUTT WELD SMS 3008 ENDS
BRANCH : DN80 HYGIENIC CLAMP END WITH SMS 3008 BORE

Drawn JRD	Date 27.02.12	UNCONTROLLED IN HARD COPY FORMAT
Checked RND	Date 27.02.12	
First Angle Projection Method E	DO NOT SCALE	Drawing No. WEB-148
		Issue. 1