



ORIENTATION AS PER P&ID DIAGRAM FOR OPTIMUM DRAINABILITY.

MAINLINE SIZE mm	A mm	B mm	C mm	D mm	ØE mm	ØF mm	BODY WEIGHT Kgs
DN65	50.0	50.0	37.2	49.0	77.4	60.3	8.5
DN80	50.0	50.0	43.5	56.0	90.9	72.9	7.9
DN100	50.0	50.0	55.8	68.0	118.9	97.6	10.3

The information on this sheet is Private and Confidential and is the property of Crane Process Flow Technologies Limited and must not be published directly or indirectly in any manner whatsoever without the written permission of the Company and must not be used in any way detrimental to their interests.  
© Crane Process Flow Technologies

**CRANE** Process Flow Technologies  
A Crane Co. Company

**Saunders**  
The Science Inside

Title  
SCHEDULE OF LEADING DIMENSIONS FOR DN65  
WEIR 'T' BODY COMPLETE WITH :  
MAINLINE : HYGIENIC CLAMP ENDS WITH SMS 3008 BORE  
BRANCH : DN65 HYGIENIC CLAMP END WITH SMS 3008 BORE

Drawn JRD	Date 27.02.12	UNCONTROLLED IN HARD COPY FORMAT	
Checked RND	Date 27.02.12		
First Angle Projection Method E	DO NOT SCALE	Drawing No. WEB-157	Issue. 1