



ORIENTATION AS PER P&ID DIAGRAM FOR OPTIMUM DRAINABILITY.

| MAINLINE SIZE | A | B | C | D | øE | øF | BODY WEIGHT |
|---------------|------|------|------|------|-------|------|-------------|
| mm | mm | mm | mm | mm | mm | mm | Kgs |
| DN80 | 50.0 | 50.0 | 46.5 | 64.0 | 90.9 | 72.9 | 21.2 |
| DN100 | 50.0 | 50.0 | 58.8 | 76.0 | 118.9 | 97.6 | 28.5 |

The information on this sheet is Private and Confidential and is the property of Crane Process Flow Technologies Limited and must not be published directly or indirectly in any manner whatsoever without the written permission of the Company and must not be used in any way detrimental to their interests.
© Crane Process Flow Technologies

CRANE Process Flow Technologies
A Crane Co. Company

Saunders
The Science Inside

Title
SCHEDULE OF LEADING DIMENSIONS FOR DN80
WEIR 'T' BODY COMPLETE WITH :
MAINLINE : HYGIENIC CLAMP ENDS WITH SMS 3008 ENDS
BRANCH : DN80 HYGIENIC CLAMP END WITH SMS 3008 BORE

Drawn JRD Date 27.02.12 UNCONTROLLED IN
Checked RND Date 27.02.12 HARD COPY FORMAT

First Angle Projection Method E DO NOT SCALE Drawing No. WEB-158 Issue. 1