


DN65 TO DN100
MAINLINE ONLY



ORIENTATION AS
PER P&ID DIAGRAM
FOR OPTIMUM
DRAINABILITY.

MAINLINE SIZE	A	B	C	D	øE	øF	G	H	BODY WEIGHT
mm	mm	mm	mm	mm	mm	mm	mm	mm	Kgs
DN65 DIN 11850 S1	120.0	50.8	40.0	52.0	70.0	66.0	38.0	392.0	10.0
DN80 DIN 11850 S1	145.0	50.8	47.5	60.0	85.0	81.0	38.0	442.0	12.9
DN100 DIN 11850 S1	155.0	50.8	57.0	69.0	104.0	100.0	38.0	462.0	16.4

The information on this sheet is Private and Confidential and is the property of Crane Process Flow Technologies Limited and must not be published directly or indirectly in any manner whatsoever without the written permission of the Company and must not be used in any way detrimental to their interests.
© Crane Process Flow Technologies

CRANE Process Flow Technologies
A Crane Co. Company

Saunders
The Science Inside

Title
SCHEDULE OF LEADING DIMENSIONS FOR DN65
WEIR 'T' BODY COMPLETE WITH :
MAINLINE : DIN 11850 S1 POINT OF USE BUTT WELD ENDS
BRANCH : DN65 DIN 11850 S1 BUTT WELD END

Drawn R1 Date 25.05.12

Checked RND Date 25.05.12

First Angle Projection Method E

UNCONTROLLED IN
HARD COPY FORMAT

Drawing No. WEB-198 Issue. 1