


MAIN LINE SIZE	A	B	C	∅D	∅E	F	G	H	BODY WEIGHT
mm	mm	mm	mm	mm	mm	mm	mm	mm	Kgs
DN15	50.8	11.0	30.8	19.0	16.0	61.5	10.5	50.0	1.1
DN20	50.8	13.0	30.8	23.0	20.0	61.5	12.5	52.5	1.2
DN25	50.8	16.0	30.8	29.0	26.0	61.5	15.5	58.5	1.3
DN32	50.8	19.0	33.9	35.0	32.0	65.0	18.5	64.5	1.3
DN40	50.8	22.0	33.4	41.0	38.0	63.0	21.5	70.5	1.4
DN50	50.8	28.0	37.8	53.0	50.0	71.0	27.5	82.5	1.7
DN65	50.8	36.0	42.5	70.0	66.0	80.0	35.5	99.0	2.1
DN80	50.8	43.5	46.7	85.0	81.0	93.0	43.0	114.0	2.2
DN100	101.6	53.0	55.0	104.0	100.0	110.0	52.5	133.0	3.2



ORIENTATION AS PER P&ID DIAGRAM FOR OPTIMUM DRAINABILITY.

The information on this sheet is Private and Confidential and is the property of Crane Process Flow Technologies Limited and must not be published directly or indirectly in any manner whatsoever without the written permission of the Company and must not be used in any way detrimental to their interests.  
 © Crane Process Flow Technologies

**CRANE** Process Flow Technologies  
 A Crane Co. Company

**Saunders**  
 The Science Inside

Title  
 SCHEDULE OF LEADING DIMENSIONS FOR DN15 WEIR 'T' BODY WITH DN8 BACK SAMPLE ALL ENDS BUTT WELD DIN 11850 S1/S2 TUBING

Drawn	NAW	Date	20.11.12	UNCONTROLLED IN HARD COPY FORMAT
Checked	JRD	Date	20.11.12	
First Angle Projection Method	E	DO NOT SCALE	Drawing No.	Issue.
			WEB-252	1