


DN65 TO DN100 MAINLINE



ORIENTATION AS PER P&ID DIAGRAM FOR OPTIMUM DRAINABILITY.

MAINLINE SIZE	A	B	C	øD	øE	F	G	H	I	BODY WEIGHT
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	Kgs
DN65	50.8	40.0	58.5	70.0	66.0	117.0	35.5	145.0	92.0	10.3
DN80	50.8	47.5	62.5	85.0	81.0	117.0	43.0	160.0	107.0	10.4
DN100	101.6	57.0	68.5	104.0	100.0	124.0	52.5	179.0	126.0	11.9

The information on this sheet is Private and Confidential and is the property of Crane Process Flow Technologies Limited and must not be published directly or indirectly in any manner whatsoever without the written permission of the Company and must not be used in any way detrimental to their interests.
© Crane Process Flow Technologies

CRANE Process Flow Technologies
A Crane Co. Company

Saunders
The Science Inside

Title
SCHEDULE OF LEADING DIMENSIONS FOR DN65
WEIR 'T' BODY WITH DN8 BACK SAMPLE
ALL ENDS BUTT WELD DIN 11850 S1/S2 TUBING

Drawn RI Date 25.05.12

UNCONTROLLED IN
HARD COPY FORMAT

Checked JRD Date 25.05.12

First Angle Projection Method E DO NOT SCALE

Drawing No. WEB-257 Issue. 1